

V5 User Teams

Last Modified on 01/28/2026 4:51 pm EST |

Page 1: AccountTeams Users Object v5

Note: The AccountTeams Users Object is only accessible to Account Administrator users.

The following API calls are currently available for the AccountTeams Users object:

- GET LIST
- ADD USERS
- UPDATE USERS
- DELETE USERS

GET LIST - Get a list of all users on a team.

```
https://api.alchemer.com/v5/accountteams/[TEAMID]/users
```

Note: Get requests will cache for 60 seconds. If you make repeated API get requests that are identical, the return will be cached and will thus return identical results.

Parameters	Example	Required
Authentication Credentials	api_token=abcd12345&api_token_secret=abcd12345	True
page	page=2	False
resultsperpage	resultsperpage=100	False

Response Example (.json format):

```
{
  "result_ok": true,
  "total_count": 2,
  "page": 1,
  "total_pages": 1,
  "results_per_page": 2,
  "data": [
    {
      "user_id": "938116",
      "username": "JF Testuser4",
      "email": "justin.falk+tu4@alchemer.com",
      "team_id": "1",
      "team_name": "Team 1",
      "is_team_manager": false,
      "role_id": "4",
      "role_name": "Editor"
    },
    {
      "user_id": "928117",
      "username": "Chris Minnich",
      "email": "chris.minnich+cid731671@alchemer.com",
      "team_id": "1",
      "team_name": "Team 1",
      "is_team_manager": false,
      "role_id": "4",
      "role_name": "Editor"
    }
  ]
}
```

ADD USERS - Add users to a team.

[https://api.alchemer.com/v5/accountteams/\[TEAMID\]/users?_method=PUT&users=\[JSON_ARRAY\]](https://api.alchemer.com/v5/accountteams/[TEAMID]/users?_method=PUT&users=[JSON_ARRAY])

Parameters	Value/Example	Required
Authentication Credentials	api_token=abcd12345&api_token_secret=abcd12345	True
users	JSON array of user objects	True

User Object Parameters:

Parameter	Description	Required
user_id	The user ID of the user to add	True
role_id	The role ID of the role to assign (2-6 for standard roles)	True
is_team_manager	Whether the user is a team manager (true/false)	False (defaults to false)

Request Example:

```
https://api.alchemer.com/v5/accountteams/123456/users?_method=PUT&api_token=abcd12345&api_token_secret=abcd12345&users=[{"user_id":"889312","role_id":"4","is_team_manager":true},{"user_id":"909455","role_id":"2"}]
```

Success Response Example (.json format):

```
{
  "result_ok": true,
  "code": 200,
  "message": "Added 2 users to team.",
  "data": [
    {
      "user_id": "889312",
      "result_ok": true,
      "code": 200,
      "message": "Added user to team."
    },
    {
      "user_id": "909455",
      "result_ok": true,
      "code": 200,
      "message": "Added user to team."
    }
  ]
}
```

Error Response Example (.json format):

```
{
  "result_ok": false,
  "code": 400,
  "message": "Failed to add all users to team. See data for details.",
  "data": [
    {
      "user_id": "889312",
      "result_ok": true,
      "code": 200,
      "message": "Added user to team."
    },
    {
      "user_id": "909455",
      "result_ok": false,
      "code": 400,
      "message": "Failed to add user to team. User id 909455 not found."
    }
  ]
}
```

UPDATE USERS - Update team properties for users on a team.

```
https://api.alchemer.com/v5/accountteams/[TEAMID]/users?_method=POST&users=[JSON_ARRAY]
```

Parameters	Value/Example	Required
------------	---------------	----------

Parameters	Value/Example	Required
Authentication Credentials	api_token=abcd12345&api_token_secret=abcd12345	True
users	JSON array of user objects	True

User Object Parameters:

Parameter	Description	Required
user_id	The user ID of the user to update	True
role_id	The role ID to assign (2-6 for standard roles)	False*
is_team_manager	Whether the user is a team manager (true/false)	False*

*At least one of role_id or is_team_manager is required.

Request Example:

```
https://api.alchemer.com/v5/accountteams/123456/users?_method=POST&api_token=abcd12345&api_token_secret=abcd12345&users=[{"user_id":"889312","role_id":"2","is_team_manager":false},{"user_id":"909455","role_id":"4"}]
```

Success Response Example (.json format):

```
{
  "result_ok": true,
  "code": 200,
  "message": "Updated 2 users on team.",
  "data": [
    {
      "user_id": "889312",
      "result_ok": true,
      "code": 200,
      "message": "Updated user on team."
    },
    {
      "user_id": "909455",
      "result_ok": true,
      "code": 200,
      "message": "Updated user on team."
    }
  ]
}
```

Error Response Example (.json format):

```
{
  "result_ok": false,
  "code": 400,
  "message": "Failed to update all users on team. See data for details.",
  "data": [
    {
      "user_id": "889312",
      "result_ok": true,
      "code": 200,
      "message": "Updated user on team."
    },
    {
      "user_id": "909455",
      "result_ok": false,
      "code": 400,
      "message": "Failed to update user. User is not a member of team id 123456."
    }
  ]
}
```

DELETE USERS - Remove users from a team.

[https://api.alchemer.com/v5/accountteams/\[TEAMID\]/users?_method=DELETE&user_ids=\[JSON_ARRAY\]](https://api.alchemer.com/v5/accountteams/[TEAMID]/users?_method=DELETE&user_ids=[JSON_ARRAY])

Parameters	Value/Example	Required
Authentication Credentials	api_token=abcd12345&api_token_secret=abcd12345	True
user_ids	JSON array of user IDs	True

Request Example:

```
https://api.alchemer.com/v5/accountteams/123456/users?_method=DELETE&api_token=abcd12345&api_token_secret=abcd12345&user_ids=["889312","909455"]
```

Alternative: JSON Body

You can also pass the user_ids as a JSON body:

```
{
  "user_ids": ["889312", "909455"]
}
```

If both query parameter and JSON body are provided, the query parameter takes precedence.

Success Response Example (.json format):

```
{
  "result_ok": true,
  "code": 200,
  "message": "Removed 2 users from team.",
  "data": [
    {
      "user_id": "889312",
      "result_ok": true,
      "code": 200,
      "message": "Removed user from team."
    },
    {
      "user_id": "909455",
      "result_ok": true,
      "code": 200,
      "message": "Removed user from team."
    }
  ]
}
```

Error Response Example (.json format):

```
{
  "result_ok": false,
  "code": 400,
  "message": "Failed to remove all users from team. See data for details.",
  "data": [
    {
      "user_id": "889312",
      "result_ok": true,
      "code": 200,
      "message": "Removed user from team."
    },
    {
      "user_id": "909455",
      "result_ok": false,
      "code": 400,
      "message": "Failed to remove user from team. User id 909455 not found."
    }
  ]
}
```

Page 2: AccountUser Teams Object v5

Note: The AccountUser Teams Object is only accessible to Account Administrator users.

The following API calls are currently available for the AccountUser Teams object:

- GET LIST
- ADD TEAMS
- UPDATE TEAMS

- DELETE TEAMS

GET LIST - Get a list of all teams for a user.

[https://api.alchemer.com/v5/accountuser/\[USERID\]/teams](https://api.alchemer.com/v5/accountuser/[USERID]/teams)

Note: Get requests will cache for 60 seconds. If you make repeated API get requests that are identical, the return will be cached and will thus return identical results.

Parameters	Example	Required
Authentication Credentials	api_token=abcd12345&api_token_secret=abcd12345	True
page	page=2	False
resultsperpage	resultsperpage=100	False

Response Example (.json format):

```
{
  "result_ok": true,
  "total_count": 2,
  "page": 1,
  "total_pages": 1,
  "results_per_page": 2,
  "data": [
    {
      "team_id": "1",
      "team_name": "Team 1",
      "user_id": "938116",
      "username": "JF Testuser4",
      "email": "justin.falk+tu4@alchemer.com",
      "is_team_manager": true,
      "role_id": "4",
      "role_name": "Editor"
    },
    {
      "team_id": "2",
      "team_name": "Team 2",
      "user_id": "938116",
      "username": "JF Testuser4",
      "email": "justin.falk+tu4@alchemer.com",
      "is_team_manager": false,
      "role_id": "2",
      "role_name": "Reporter"
    }
  ]
}
```

ADD TEAMS - Add a user to teams.

[https://api.alchemer.com/v5/accountuser/\[USERID\]/teams?_method=PUT&teams=\[JSON_ARRAY\]](https://api.alchemer.com/v5/accountuser/[USERID]/teams?_method=PUT&teams=[JSON_ARRAY])

Parameters	Value/Example	Required
------------	---------------	----------

Parameters	Value/Example	Required
Authentication Credentials	api_token=abcd12345&api_token_secret=abcd12345	True
teams	JSON array of team objects	True

Team Object Parameters:

Parameter	Description	Required
team_id	The team ID of the team to add the user to	True
role_id	The role ID of the role to assign (2-6 for standard roles)	True
is_team_manager	Whether the user is a team manager (true/false)	False (defaults to false)

Request Example:

```
https://api.alchemer.com/v5/accountuser/938116/teams?_method=PUT&api_token=abcd12345&api_token_secret=abcd12345&teams=[{"team_id":"1","role_id":"4","is_team_manager":true},{"team_id":"2","role_id":"2"}]
```

Success Response Example (.json format):

```
{
  "result_ok": true,
  "code": 200,
  "message": "Added user to 2 teams.",
  "data": [
    {
      "team_id": "1",
      "result_ok": true,
      "code": 200,
      "message": "Added user to team."
    },
    {
      "team_id": "2",
      "result_ok": true,
      "code": 200,
      "message": "Added user to team."
    }
  ]
}
```

Error Response Example (.json format):


```
{
  "result_ok": false,
  "code": 400,
  "message": "Failed to add user to all teams. See data for details.",
  "data": [
    {
      "team_id": "1",
      "result_ok": true,
      "code": 200,
      "message": "Added user to team."
    },
    {
      "team_id": "42",
      "result_ok": false,
      "code": 400,
      "message": "Team id 42 not found."
    }
  ]
}
```

UPDATE TEAMS - Update team properties for a user.

[https://api.alchemer.com/v5/accountuser/\[USERID\]/teams?_method=POST&teams=\[JSON_ARRAY\]](https://api.alchemer.com/v5/accountuser/[USERID]/teams?_method=POST&teams=[JSON_ARRAY])

Parameters	Value/Example	Required
Authentication Credentials	api_token=abcd12345&api_token_secret=abcd12345	True
teams	JSON array of team objects	True

Team Object Parameters:

Parameter	Description	Required
team_id	The team ID of the team to update	True
role_id	The role ID to assign (2-6 for standard roles)	False*
is_team_manager	Whether the user is a team manager (true/false)	False*

*At least one of role_id or is_team_manager is required.

Request Example:

```
https://api.alchemer.com/v5/accountuser/938116/teams?_method=POST&api_token=abcd12345&api_token_secret=abcd12345&teams=[{"team_id":"1","role_id":"2","is_team_manager":false}, {"team_id":"2","role_id":"4"}]
```

Success Response Example (json format):

```
{
  "result_ok": true,
  "code": 200,
  "message": "Updated user on 2 teams.",
  "data": [
    {
      "team_id": "1",
      "result_ok": true,
      "code": 200,
      "message": "Updated user on team."
    },
    {
      "team_id": "2",
      "result_ok": true,
      "code": 200,
      "message": "Updated user on team."
    }
  ]
}
```

Error Response Example (.json format):

```
{
  "result_ok": false,
  "code": 400,
  "message": "Failed to update user on all teams. See data for details.",
  "data": [
    {
      "team_id": "1",
      "result_ok": true,
      "code": 200,
      "message": "Updated user on team."
    },
    {
      "team_id": "3",
      "result_ok": false,
      "code": 400,
      "message": "Failed to update. User is not a member of team id 3."
    }
  ]
}
```

DELETE TEAMS - Remove a user from teams.

[https://api.alchemer.com/v5/accountuser/\[USERID\]/teams?_method=DELETE&team_ids=\[JSON_ARRAY\]](https://api.alchemer.com/v5/accountuser/[USERID]/teams?_method=DELETE&team_ids=[JSON_ARRAY])

Parameters	Value/Example	Required
Authentication Credentials	api_token=abcd12345&api_token_secret=abcd12345	True
team_ids	JSON array of team IDs	True

Request Example:

[https://api.alchemer.com/v5/accountuser/938116/teams?_method=DELETE&api_token=abcd12345&api_token_secret=abcd12345&team_ids=\["1","3"\]](https://api.alchemer.com/v5/accountuser/938116/teams?_method=DELETE&api_token=abcd12345&api_token_secret=abcd12345&team_ids=[)

Alternative: JSON Body

You can also pass the team_ids as a JSON body:

```
{
  "team_ids": ["1", "3"]
}
```

If both query parameter and JSON body are provided, the query parameter takes precedence.

Success Response Example (.json format):

```
{
  "result_ok": true,
  "code": 200,
  "message": "Removed user from 2 teams.",
  "data": [
    {
      "team_id": "1",
      "result_ok": true,
      "code": 200,
      "message": "Removed user from team."
    },
    {
      "team_id": "3",
      "result_ok": true,
      "code": 200,
      "message": "Removed user from team."
    }
  ]
}
```

Error Response Example (.json format):

```
{
  "result_ok": false,
  "code": 400,
  "message": "Failed to remove user from all teams. See data for details.",
  "data": [
    {
      "team_id": "1",
      "result_ok": true,
      "code": 200,
      "message": "Removed user from team."
    },
    {
      "team_id": "42",
      "result_ok": false,
      "code": 400,
      "message": "Failed to remove user from team. Team id 42 not found."
    }
  ]
}
```

Standard Roles Reference

The following standard role IDs are available:

Role ID	Role Name
2	Reporter
3	Builder
4	Editor
5	Standard
6	Admin

Custom roles will have IDs greater than 6.
