

# Get Account User

Returns detailed information about a single account user.

## Endpoint

**GET** v5/accountuser/{user\_id}

Requires authentication.

## Path Parameters

The account user to retrieve.

### **user\_id**

*string*

*required*

The ID of the account user to retrieve.

## Query Parameters

This endpoint does not accept additional query parameters beyond authentication credentials.

None

## Response

Returns a single account user object.

### **result\_ok**

*boolean*

Whether the request succeeded.

### **data**

*object*

The account user object.

- ▼ child attributes

#### **id**

*string*

The unique ID of the user.

**username***string*

The user's display name.

**email***string*

The user's email address.

**admin***integer*

Whether the user has account administrator privileges. `1` = admin, `0` = standard user.

**phone\_support***integer*

Whether phone support access is enabled for the user. `1` = enabled, `0` = disabled.

**userdata***array | object*

Custom user data fields set on the user. Returns an empty array `[]` if none are set.

**license***string*

The license type assigned to the user (e.g. `Full Access`, `Professional`, `Collaborator`, `Stakeholder`).

**defaultteam***integer | boolean*

The ID of the user's default team, or `false` if no default team is set.

**status***string | null*

The user's account status. Possible values: `Active`, `Disabled`, or `null`.

**last\_login***string | null*

Timestamp of the user's most recent login (EST/EDT), or `null` if the user has not yet logged in.

**api\_key**

*string | null*

The user's API token, if one has been generated. Returns `null` if no token exists.

### **api\_secret**

*string | null*

The user's API token secret, if one has been generated. Returns `null` if no token exists.

## Examples

NOTE GET requests are cached for 60 seconds. Repeated identical requests within that window will return cached results.

### REQUEST (CURL)

```
curl -X GET "https://api.alchemer.com/v5/accountuser/{{user_id}}?api_token=YOUR_API_TOKEN&api_token_secret=YOUR_API_TOKEN_SECRET"
```

### RESPONSE

```
{
  "result_ok": true,
  "data": {
    "id": "123456",
    "username": "Jane Smith",
    "email": "jane.smith@example.com",
    "admin": 1,
    "phone_support": 0,
    "userdata": [],
    "license": "Full Access",
    "defaultteam": "true",
    "status": "Active",
    "last_login": "2026-04-06 10:39:20",
    "api_key": "YOUR_API_TOKEN",
    "api_secret": "YOUR_API_TOKEN_SECRET"
  }
}
```