

# Create Account User

Creates a new user in your account.

## Endpoint

**PUT** v5/accountuser

Requires authentication.

## Path Parameters

None

## Query Parameters

### email

*string*

*required*

The email address for the new user.

### username

*string*

The display name for the new user.

### team

*integer*

The ID of a team to add the user to.

### defaultteam

*integer*

The ID of the team to set as the user's default team.

### admin

*integer*

Whether to grant account administrator privileges. Accepted values:  (admin),  (standard user).

### phone\_support

*integer*

Whether to enable phone support access. Accepted values:  (enabled),  (disabled).

## license

*string*

The license type to assign to the user. Accepted values:  ,  ,  ,  .

## create\_access\_token

*boolean*

Whether to generate an API access token for the new user. Only allowed when using OAuth authentication. Accepted value:  .

## userdata

*object*

Custom user data fields to set on the new user. Each key is the column name of the custom field.

- ▼ child attributes

### column\_name

*string*

The value to set for the named custom field. Example:  .

## Response

Returns the newly created account user object.

## result\_ok

*boolean*

Whether the request succeeded.

## data

*object*

The newly created account user object.

- ▼ child attributes

### id

*string*

The unique ID of the newly created user.

**username***string*

The user's display name.

**email***string*

The user's email address.

**status***string*

The user's account status. Possible values: `Active` , `Disabled` .

**api\_key***string / null*

The user's API token. Populated only if `create_access_token=true` was passed; otherwise `null` .

**api\_secret***string / null*

The user's API token secret. Populated only if `create_access_token=true` was passed; otherwise `null` .

## Examples

**REQUEST (CURL)**

```
curl -X PUT "https://api.alchemer.com/v5/accountuser?api_token=YOUR_API_TOKEN&api_token_secret=YOUR_API_TOKEN_SECRET&email=newuser@example.com&username=Jane+Doe&license=Full+Access"
```

**RESPONSE**

```
{
  "result_ok": true,
  "data": {
    "id": "YOUR_USER_ID",
    "username": "Jane Doe",
    "email": "newuser@example.com",
    "admin": 0,
    "phone_support": 0,
    "userdata": [],
    "license": "Full Access",
    "defaultteam": false,
    "status": "Active",
    "last_login": null,
    "api_key": null,
    "api_secret": null
  }
}
```