

Update Account User

Updates information for a specific user in your account.

Endpoint

POST v5/accountuser/{user_id}

Requires authentication.

Path Parameters

The user to update.

user_id

string

required

The ID of the account user to update.

Query Parameters

email

string

A new email address for the user.

username

string

A new display name for the user.

team

integer

The ID of a team to add the user to.

defaultteam

integer

The ID of the team to set as the user's default team.

admin

integer

Whether to grant account administrator privileges. Accepted values: (admin), (standard)

user).

phone_support

integer

Whether to enable phone support access. Accepted values: `1` (enabled), `0` (disabled).

userstatus

string

The account status to set for the user. Accepted values: `Active` , `Disabled` .

license

string

The license type to assign to the user. Accepted values: `Full Access` , `Reporting` , `Market Researcher` , `Educational` , `HR Professional` , `Basic` , `Standard` .

userdata

object

Custom user data fields to update. Each key is the column name of the custom field.

- ▼ child attributes

column_name

string

The value to set for the named custom field. Example: `userdata[department]=sales` .

Response

Returns the updated account user object.

result_ok

boolean

Whether the request succeeded.

data

object

The updated account user object.

- ▼ child attributes

id

string

The unique ID of the user.

username

string

The user's display name after the update.

email

string

The user's email address after the update.

admin

integer

Whether the user has account administrator privileges. `1` = admin, `0` = standard user.

phone_support

integer

Whether phone support access is enabled for the user. `1` = enabled, `0` = disabled.

userdata

array | object

Custom user data fields set on the user. Returns an empty array `[]` if none are set.

license

string

The license type assigned to the user after the update.

defaultteam

string | boolean

The ID of the user's default team, or `false` if no default team is set.

status

string | null

The user's account status after the update. Possible values: `Active`, `Disabled`, or `null`.

last_login

string | null

Timestamp of the user's most recent login (EST/EDT), or `null` if the user has not yet logged in.

api_key

string / null

The user's API token, if one has been generated. Returns `null` if no token exists.

api_secret

string / null

The user's API token secret, if one has been generated. Returns `null` if no token exists.

Examples

REQUEST (CURL)

```
curl -X POST "https://api.alchemer.com/v5/accountuser/{{user_id}}?api_token=YOUR_API_TOKEN&api_token_secret=YOUR_API_TOKEN_SECRET&userstatus=Active"
```

RESPONSE

```
{
  "result_ok": true,
  "data": {
    "id": "123456",
    "username": "Jane Smith",
    "email": "jane.smith@example.com",
    "admin": 1,
    "phone_support": 0,
    "userdata": [],
    "license": "Full Access",
    "defaultteam": "1000125",
    "status": "Active",
    "last_login": "2026-04-06 10:39:20",
    "api_key": "YOUR_API_TOKEN",
    "api_secret": "YOUR_API_TOKEN_SECRET"
  }
}
```