

Delete Account User

Deletes a specific user from your account.

Endpoint

DELETE v5/accountuser/{user_id}

Requires authentication.

Path Parameters

The user to delete.

user_id

string

required

The ID of the account user to delete.

Query Parameters

None

Response

Returns the deleted user's record with their status set to `Disabled`.

result_ok

boolean

Whether the request succeeded.

data

object

The account user record after deletion.

- ▼ child attributes

id

string

The unique ID of the deleted user.

username*string*

The user's display name.

email*string*

The user's email address.

admin*integer*

Whether the user had account administrator privileges. `1` = admin, `0` = standard user.

phone_support*integer*

Whether phone support access was enabled for the user. `1` = enabled, `0` = disabled.

userdata*array | object*

Custom user data fields set on the user. Returns an empty array `[]` if none are set.

license*string*

The license type that was assigned to the user. Returns an empty string if no license was assigned.

defaultteam*string | boolean*

The ID of the user's default team, or `false` if no default team was set.

status*string*

The user's account status after deletion. Returns `Disabled`.

last_login*string | null*

Timestamp of the user's most recent login (EST/EDT), or `null` if the user never logged in.

Examples

REQUEST (CURL)

```
curl -X DELETE "https://api.alchemer.com/v5/accountuser/{{user_id}}?api_token=YOUR_API_TOKEN&api_token_secret=YOUR_API_TOKEN_SECRET"
```

RESPONSE

```
{
  "result_ok": true,
  "data": {
    "id": "123456",
    "username": "user@example.com",
    "email": "user@example.com",
    "admin": 0,
    "phone_support": 0,
    "userdata": [],
    "license": "",
    "defaultteam": false,
    "status": "Disabled",
    "last_login": null
  }
}
```