

# Create Contact List Contact

Creates a new contact inside a specified contact list.

## Endpoint

**PUT** v5/contactlist/{list\_id}/contactlistcontact

Requires authentication

## Path Parameters

The contact list to add the contact to.

### **list\_id**

*string*

*required*

The ID of the contact list.

## Query Parameters

### **email\_address**

*string*

*required*

The contact's email address.

### **status**

*string*

The contact's status. Values: `Active`, `Inactive`.

### **first\_name**

*string*

The contact's first name.

### **last\_name**

*string*

The contact's last name.

### **organization**

*string*

The contact's organization.

### **division**

*string*

The contact's division.

### **department**

*string*

The contact's department.

### **group**

*string*

The contact's group.

### **role**

*string*

The contact's role.

### **is\_manager**

*boolean*

Whether the contact is a manager.

### **team**

*string*

The contact's team.

### **home\_phone**

*string*

The contact's home phone number.

### **fax\_phone**

*string*

The contact's fax number.

### **business\_phone**

*string*

The contact's business phone number.

### **mailing\_address**

*string*

The contact's mailing address (line 1).

## **mailing\_address2**

*string*

The contact's mailing address (line 2).

## **mailing\_address\_city**

*string*

The contact's city.

## **mailing\_address\_state**

*string*

The contact's state or province.

## **mailing\_address\_postal**

*string*

The contact's postal or ZIP code.

## **mailing\_address\_country**

*string*

The contact's country code. Example: `US` .

## **title**

*string*

The contact's job title.

## **url**

*string*

The contact's website URL.

## **custom**

*object*

Custom fields defined in the contact list. Each key is the numeric custom field ID.

- ▼ child attributes

### **{field\_id}**

*string*

The value to set for the custom field with the given numeric ID. Example: `custom[15]=value` .

*Custom field IDs are account-specific. To find custom field IDs for your contact list, use the [Contact Custom Field endpoint](#).*

## Response

Returns the result of the creation request and the newly created contact object.

### **result\_ok**

*boolean*

Whether the request succeeded.

### **data**

*object*

The newly created contact object. See [List Contact List Contacts](#) for the full list of response fields.

## Examples

### REQUEST (CURL)

```
curl -X PUT "https://api.alchemer.com/v5/contactlist/YOUR_LIST_ID/contactlistcontact?api_token=YOUR_API_TOKEN&api_token_secret=YOUR_API_TOKEN_SECRET&email_address=jon.doe%40example.com&first_name=Jon&last_name=Doe"
```

### RESPONSE

```
{
  "result_ok": true,
  "data": {
    "id": 100012345,
    "email_address": "jon.doe@example.com",
    "status": "Active",
    "first_name": "Jon",
    "last_name": "Doe",
    "organization": "",
    "division": "",
    "department": "",
    "group": "",
    "role": "",
    "is_manager": false,
    "team": "",
    "home_phone": "",
    "fax_phone": "",
    "business_phone": "",
    "mailing_address": "",
    "mailing_address2": "",
    "mailing_address_city": "",
    "mailing_address_state": "",
    "mailing_address_postal": "",
    "mailing_address_country": "",
    "title": "",
    "url": ""
  }
}
```