

Update Contact List Contact

Updates a contact within a specified contact list. The contact is identified by email address. Include only the fields you want to change.

Endpoint

POST v5/contactlist/{list_id}/contactlistcontact

Requires authentication

Path Parameters

The contact list containing the contact to update.

list_id

string

required

The ID of the contact list.

Query Parameters

email_address

string

required

The email address of the contact to update. Used to identify the contact.

status

string

Updated status. Values: `Active` , `Inactive` .

first_name

string

Updated first name.

last_name

string

Updated last name.

organization

string

Updated organization.

division

string

Updated division.

department

string

Updated department.

group

string

Updated group.

role

string

Updated role.

is_manager

boolean

Updated manager flag.

team

string

Updated team.

home_phone

string

Updated home phone number.

fax_phone

string

Updated fax number.

business_phone

string

Updated business phone number.

mailing_address

string

Updated mailing address (line 1).

mailing_address2

string

Updated mailing address (line 2).

mailing_address_city

string

Updated city.

mailing_address_state

string

Updated state or province.

mailing_address_postal

string

Updated postal or ZIP code.

mailing_address_country

string

Updated country code. Example: `US`.

title

string

Updated job title.

url

string

Updated website URL.

custom

object

Custom fields to update. Each key is the numeric custom field ID.

- ▼ child attributes

{field_id}

string

The updated value for the custom field with the given numeric ID. Example:

```
custom[15]=value .
```

Custom field IDs are account-specific. To find custom field IDs for your contact list, use the [Contact Custom Field](#) endpoint.

Response

Returns the updated contact object.

result_ok

boolean

Whether the request succeeded.

data

object

The updated contact object. See [List Contact List Contacts](#) for the full list of response fields.

Examples

REQUEST (CURL)

```
curl -X POST "https://api.alchemer.com/v5/contactlist/YOUR_LIST_ID/contactlistcontact?api_token=YOUR_API_TOKEN&api_token_secret=YOUR_API_TOKEN_SECRET&email_addresses=jon.doe%40example.com&first_name=Jonathan"
```

RESPONSE

```
{
  "result_ok": true,
  "data": {
    "id": 100039767,
    "email_address": "jon.doe@example.com",
    "status": "Active",
    "first_name": "Jonathan",
    "last_name": "Doe",
    "organization": "",
    "division": "",
    "department": "",
    "group": "",
    "role": "",
    "is_manager": false,
    "team": "",
    "home_phone": "",
    "fax_phone": "",
    "business_phone": "",
    "mailing_address": "",
    "mailing_address2": "",
    "mailing_address_city": "",
    "mailing_address_state": "",
    "mailing_address_postal": "",
    "mailing_address_country": "",
    "title": "",
    "url": ""
  }
}
```