

List Contact Custom Fields

Returns a list of all contact custom fields defined in your account. Custom field IDs returned here are used to set or retrieve custom field values on contacts via the Contact List Contact endpoints.

Endpoint

GET v5/contactcustomfield

Requires authentication

Path Parameters

This endpoint does not include path parameters.

None

Query Parameters

All query parameters are optional.

page

integer

Page number to return. Defaults to 1.

resultsperpage

integer

Number of results to return per page. Default is 50, maximum is 500.

Response

Returns a keyed object of contact custom field objects, where each key is the field ID.

result_ok

boolean

Whether the request succeeded.

data

object

Keyed object of custom field objects, where each key is the field's numeric ID string.

- ▼ child attributes

id

string

The unique numeric ID of the custom field.

name

string

The name of the custom field.

type

string

The data type of the custom field. Values: `Text` , `Date/Time` , `Currency` , `Number` , `Yes/No` .

Examples

NOTE GET requests are cached for 60 seconds. Repeated identical requests within that window will return cached results.

REQUEST (CURL)

```
curl -X GET "https://api.alchemer.com/v5/contactcustomfield?api_token=YOUR_API_TOKEN&api_token_secret=YOUR_API_TOKEN_SECRET"
```

RESPONSE

```
{
  "result_ok": true,
  "data": {
    "1": {
      "id": "1",
      "name": "customer_id",
      "type": "Number"
    },
    "2": {
      "id": "2",
      "name": "subscription_type",
      "type": "Text"
    },
    "3": {
      "id": "3",
      "name": "renewal_date",
      "type": "Date/Time"
    }
  }
}
```