

Get Email Message

Returns detailed information about a specific email message within a survey campaign.

Endpoint

GET v5/survey/{survey_id}/surveycampaign/{campaign_id}/emailmessage/{message_id}

Requires authentication

Path Parameters

Identifies the survey, campaign, and specific message to retrieve.

survey_id

string

required

The ID of the survey.

campaign_id

string

required

The ID of the survey campaign.

message_id

string

required

The ID of the email message to retrieve.

Query Parameters

This endpoint does not accept additional query parameters beyond authentication credentials.

None

Response

Returns a single email message object.

result_ok

boolean

Whether the request succeeded.

data

object

The email message object.

- ▼ child attributes

id

integer

The unique ID of the email message.

subtype

string

The message subtype. Possible values: `message` , `reminder` .

message_type

string

The format of the message. Possible values: `plaintext` , `html` .

medium

string

The delivery medium. Always `Email` .

invite_identity

integer

The internal ID of the campaign (invite identity) this message belongs to.

status

string

The current send status of the message (e.g. `Building` , `Sent`).

from

object

The sender details for the message.

- ▼ child attributes

email

string

The sender's email address.

name

string

The sender's display name.

subject

string

The email subject line.

body

object

The message body content.

- ▼ child attributes

text

string

The plaintext version of the message body.

html

string

The HTML version of the message body. Empty string if the message is plaintext only.

footer

string

The message footer text, typically including the physical address and unsubscribe link merge codes.

embed_question

boolean

Whether the first survey question is embedded in the email body.

disable_styles

boolean

Whether default email message styles are disabled.

date_created

string

Timestamp when the message was created.

date_modified

string

Timestamp when the message was last modified.

Examples

NOTE GET requests are cached for 60 seconds. Repeated identical requests within that window

will return cached results.

REQUEST (CURL)

```
curl -X GET "https://api.alchemer.com/v5/survey/123456/surveycampaign/100000/email
message/128073?api_token=YOUR_API_TOKEN&api_token_secret=YOUR_API_TOKEN_SE
CRET"
```

RESPONSE

```
{
  "result_ok": true,
  "data": {
    "id": 128073,
    "subtype": "message",
    "message_type": "html",
    "medium": "Email",
    "invite_identity": 94135,
    "status": "Building",
    "from": {
      "email": "surveys@sgizmo.com",
      "name": "Survey Research"
    },
    "subject": "Please take our survey",
    "body": {
      "text": "Hi\nI'm currently running a study...\n\n[invite(\"survey link\")]\n\nThank You!",
      "html": "Hi\n\nI'm currently running a study...\n\n[invite(\"html link\"), title=\"Begin\"]\n\nThank You!"
    },
    "footer": "This message was sent by [account(\"physical address\")].\nTo unsubscribe,
click below:\n[invite(\"unsubscribe link\")]",
    "embed_question": null,
    "disable_styles": null,
    "date_created": "2014-07-29 11:25:54",
    "date_modified": "2016-05-24 14:53:33"
  }
}
```