

List Survey Campaigns

Returns a paginated list of all links and campaigns for the specified survey.

Endpoint

GET v5/survey/{survey_id}/surveycampaign

Requires authentication

Path Parameters

The survey whose campaigns should be retrieved.

survey_id

string

required

The ID of the survey whose campaigns will be listed.

Query Parameters

All query parameters are optional.

page

integer

Page number to return. Defaults to 1.

resultsperpage

integer

Number of results to return per page. Default is 50, maximum is 500.

Response

Returns a paginated array of campaign objects.

result_ok

boolean

Whether the request succeeded.

total_count

string

Total number of campaigns for the survey.

page

integer

Current page index.

total_pages

integer

Number of available pages.

results_per_page

integer

Number of results returned per page.

data

array

Array of campaign objects.

- ▼ child attributes

id

string

The unique ID of the campaign.

invite_id

string | null

The invite ID associated with email campaigns. `null` for link-type campaigns.

type

string

The object type. Always `SurveyCampaign` .

link_type

string

The broad type of the campaign. Possible values: `link` , `email` .

subtype

string

The campaign subtype. Possible values: `standard` , `hiddenlink` , `private` , `shortlink` , `subdomain` .

status

string

The campaign status. Possible values: `Active` , `Closed` , `Deleted` .

name

string

The display name of the campaign.

uri

string

The public URL of the survey link.

SSL

string

Whether SSL is enabled for the link. Returns `"True"` or `"False"` .

token_variables

string | null

URL-encoded token variables attached to the campaign link, if any.

limit_responses

integer | null

The maximum number of responses allowed through this campaign, if set.

close_message

string | null

The message displayed when the campaign is closed, if configured.

link_open_date

string | null

The scheduled open date for the campaign link, in `Y-m-d H:i:s` format.

link_close_date

string | null

The scheduled close date for the campaign link, in `Y-m-d H:i:s` format.

language

string

The language setting for the campaign. `Auto` detects the respondent's browser language.

date_created*string*

Timestamp when the campaign was created.

date_modified*string*

Timestamp when the campaign was last modified.

Examples

NOTE GET requests are cached for 60 seconds. Repeated identical requests within that window will return cached results.

REQUEST (CURL)

```
curl -X GET "https://api.alchemer.com/v5/survey/123456/surveycampaign?api_token=YOUR_API_TOKEN&api_token_secret=YOUR_API_TOKEN_SECRET"
```

RESPONSE

```
{
  "result_ok": true,
  "total_count": "9",
  "page": 1,
  "total_pages": 1,
  "results_per_page": 50,
  "data": [
    {
      "id": "300865",
      "invite_id": null,
      "type": "SurveyCampaign",
      "link_type": "link",
      "subtype": "standard",
      "status": "Active",
      "name": "Default Link",
      "uri": "www.alchemer.com/s3/1234567/survey",
      "SSL": "False",
      "primary_theme_options": null,
      "primary_theme_content": null,
      "token_variables": null,
      "limit_responses": null,
      "close_message": null,
      "link_open_date": null,
      "link_close_date": null,
      "language": "Auto",
```

```
"date_created": "2017-10-02 15:41:41",
"date_modified": "2017-10-02 15:41:41"
},
{
  "id": "300866",
  "invite_id": null,
  "type": "SurveyCampaign",
  "link_type": "link",
  "subtype": "hiddenlink",
  "status": "Active",
  "name": "Hidden Link",
  "uri": "www.alchemer.com/s3/1234567/survey",
  "SSL": "False",
  "primary_theme_options": null,
  "primary_theme_content": null,
  "token_variables": null,
  "limit_responses": null,
  "close_message": null,
  "link_open_date": null,
  "link_close_date": null,
  "language": "Auto",
  "date_created": "2017-10-02 15:41:49",
  "date_modified": "2017-10-02 15:41:49"
}
]
}
```