

List Survey Contacts

Returns a list of all contacts for the specified survey campaign.

Endpoint

GET

v5/survey/{survey_id}/surveycampaign/{campaign_id}/surveycontact

Requires authentication

Path Parameters

The survey and campaign whose contacts should be retrieved.

survey_id

string

required

The ID of the survey.

campaign_id

string

required

The ID of the survey campaign.

Query Parameters

All query parameters are optional.

page

integer

Page number to return. Defaults to 1.

resultsperpage

integer

Number of results to return per page. Default is 50, maximum is 500.

Response

Returns a paginated list of contact objects for the campaign.

result_ok

boolean

Whether the request succeeded.

total_count

integer

Total number of contacts in the campaign.

page

integer

Current page index.

total_pages

integer

Number of available pages.

results_per_page

integer

Number of results returned per page.

data

array

Array of contact objects.

- ▼ child attributes

id

integer

The unique ID of the contact.

email_address

string

The contact's email address. Used as the unique key per account.

first_name

string

The contact's first name.

last_name

string

The contact's last name.

organization

string

The contact's organization.

division

string

The contact's division.

department

string

The contact's department.

team

string

The contact's team.

group

string

The contact's group.

role

string

The contact's role.

home_phone

string

The contact's home phone number.

fax_phone

string

The contact's fax number.

business_phone

string

The contact's business phone number.

mobilephone

string

The contact's mobile phone number.

mailing_address

string

The contact's street address.

mailing_address2

string

The contact's secondary address line (e.g. suite number).

mailing_address_city

string

The contact's city.

mailing_address_state

string

The contact's state or region.

mailing_address_country

string

The contact's country.

mailing_address_postal

string

The contact's postal code.

title

string

The contact's job title.

url

string

A URL associated with the contact.

customfield1-10

string

Custom fields 1–10 available as part of the email campaign contact list.

status

string

The contact's status. Possible values: `Active` , `Inactive` .

subscriber_status

string

A combination of status log response status and send status. Possible values: `Unsent` , `Sent` , `Bounced` , `Unsubscribed` , `Partial` (link clicked and at least one page submitted), `Complete` (link clicked and response completed).

date_last_sent

string

Timestamp of when the campaign email was last sent to this contact. Empty string if never sent.

Examples

NOTE GET requests are cached for 60 seconds. Repeated identical requests within that window will return cached results.

REQUEST (CURL)

```
curl -X GET "https://api.alchemer.com/v5/survey/123456/surveycampaign/100000/surveycontact?api_token=YOUR_API_TOKEN&api_token_secret=YOUR_API_TOKEN_SECRET"
```

RESPONSE

```
{
  "result_ok": true,
  "total_count": 2,
  "page": 1,
  "total_pages": 1,
  "results_per_page": 50,
  "data": [
    {
      "id": 100039753,
      "email_address": "jon.doe@alchemer.com",
      "first_name": "Jon",
      "last_name": "Doe",
      "organization": "",
      "division": "",
      "department": "",
      "team": "",
      "group": "",
      "role": "",
      "home_phone": "",
      "fax_phone": "",
      "business_phone": "",
      "mobilephone": "",
      "mailing_address": "",
      "mailing_address2": "",
      "mailing_address_city": "",
      "mailing_address_state": "",
      "mailing_address_country": "",
      "mailing_address_postal": "",
      "title": "Vice President",
      "url": "",
      "customfield1": "sales",
      "customfield2": "",
      "status": "Active",
      "subscriber_status": "Unsent",
      "date_last_sent": ""
    }
  ]
}
```