

# Update Survey Contact

Updates a specified contact within a survey campaign. One or more fields may be changed in a single call.

## Endpoint

**POST** v5/survey/{survey\_id}/surveycampaign/{campaign\_id}/surveycontact/{contact\_id}

Requires authentication

## Path Parameters

Identifies the survey, campaign, and specific contact to update.

### survey\_id

*string*

*required*

The ID of the survey.

### campaign\_id

*string*

*required*

The ID of the survey campaign.

### contact\_id

*string*

*required*

The ID of the contact to update.

## Query Parameters

All parameters are optional except `email_address`. Include only the fields you want to update.

### email\_address

*string*

*required*

The contact's email address. Changes to standard contact fields for an existing email address are applied globally across all campaigns.

### first\_name

*string*

The contact's first name.

**last\_name***string*

The contact's last name.

**organization***string*

The contact's organization.

**division***string*

The contact's division.

**department***string*

The contact's department.

**team***string*

The contact's team.

**group***string*

The contact's group.

**role***string*

The contact's role.

**home\_phone***string*

The contact's home phone number.

**fax\_phone***string*

The contact's fax number.

**business\_phone***string*

The contact's business phone number.

**mobilephone**

*string*

The contact's mobile phone number. Used when updating contacts via an SMS campaign.

### **mailing\_address**

*string*

The contact's street address.

### **mailing\_address2**

*string*

The contact's secondary address line.

### **mailing\_address\_city**

*string*

The contact's city.

### **mailing\_address\_state**

*string*

The contact's state or region.

### **mailing\_address\_country**

*string*

The contact's country.

### **mailing\_address\_postal**

*string*

The contact's postal code.

### **title**

*string*

The contact's job title.

### **url**

*string*

A URL associated with the contact.

### **customfield1-10**

*string*

Custom fields 1–10 for the email campaign contact list. Pass individually as `customfield1` , `customfield2` , etc.

### **custom[fieldname]**

*string*

Custom fields from your account email lists. Example: `custom[customerid]=value` . To find field names, go to [Account > Email Lists > Manage Custom Fields](#)

## status

*string*

The contact's status. Accepted values: `Active` , `Inactive` . Setting to `Inactive` will unsubscribe the contact from the campaign.

## Response

Returns the updated contact object. See [List Survey Contacts](#) for the full list of response fields.

## result\_ok

*boolean*

Whether the request succeeded.

## data

*object*

The updated contact object.

## Examples

### REQUEST (CURL)

```
curl -X POST "https://api.alchemer.com/v5/survey/123456/surveycampaign/100000/surveycontact/100039753?api_token=YOUR_API_TOKEN&api_token_secret=YOUR_API_TOKEN_SECRET&email_address=jon.doe@alchemer.com&title=Director"
```

### RESPONSE

```
{
  "result_ok": true,
  "data": {
    "id": 100039753,
    "email_address": "jon.doe@alchemer.com",
    "first_name": "Jon",
    "last_name": "Doe",
    "title": "Director",
    "status": "Active",
    "subscriber_status": "Unsent",
    "date_last_sent": ""
  }
}
```